

17" Panel-pc med stålfrent, Intel Core i3 / i5 / i7
med 2x PCIe-udvidelse (kan leveres med 1000nits)

FEATURES

- ✘ 17" TFT-LCD 1280x1024
- Panel montering
- Touch: Standard projiceret kapacitiv, på bestilling:
Resistiv eller glas
- Kontrast 800:1 standard (på bestilling: 1000:1
nits)
- 8. generations Intel Core Celeron, I3, I5, I7
understøttelse
- 1 x 260-bens DDR4 SO-DIMM-stik op til 32GB
2400MHz
- 4x USB 3.0 type A
- 2x GbE LAN
- Lyd ind/ud
- IP66 foran
- 1 x HDMI
- 1 x VGA
- 2x 2,5" SATA RAID 0,1,5 understøttelse
- 3x COM (1xDB9 RS-232/422/485, 1x DB9 RS232, 1x
DB9 RS-422/485)
- 1 x Mini PCIe fuld størrelse (PCIe/USB/SATA)
- 1 x Mini PCIe halv størrelse (PCIe/USB)
- 1x SIM-slot til (wifi/BT/4G)
- 1x PCIe1 og 1x PCIe x16 slot.
- 439x348x64,8mm
- CE/FCC klasse A
- Arbejdstemperatur 0~50 grader
- Mulighed for ekstern ON/OFF via. 2-polet stik
- Bredt område DC 9 ~ 36V strømindgang
- Understøtter Windows 10 IoT, Windows 11



SPECIFICATIONS

Approval	:	CE / FCC Class A
Dimensioner	:	439x348x95mm
Ethernet	:	2 x GbE LAN RJ-45
Forsyning	:	DC 9~36Vdc
IP-Tæthed	:	Front IP 66
Luftfugtighed	:	10 to 90% @ 40°C, non- condensing
Lyd	:	1 x Mic-in, Line-out
OS SUPPORT	:	WIN 7, Windows 8.1, Windows 10 IOT Enterprise
Porte	:	1xDB9 RS232, 1xDB9RS232/422/485, 1x RS422/485
Skærm	:	LCD Size 17" TFT-LCD Max. resolution 1280 x 1024 Max. color 16.7M Luminance(cd/m ²) 350 Viewangle(H°/V°) 170 (H) / 160 (V) Contrast 1000: 1 Backlight lifetime(hrs) 30,000 hrs
SSD	:	2x2.5" HDD/SSD
Temperatur	:	Operating temperature(°C) 0~50°C Storage temperature(°C)



IPP17-I8+PCIEX

SPECIFICATIONS

USB : 4 x USB 3.0 Type A, 2 x USB 2.0 Type A by cable (option)

Vægt : 7.6Kg