

Embedded PC i3/i5/i7, Celeron, 2 x HDMI, 1 x DP,
4xGbit, 6 USB 6th/7th Gen. CPU

FEATURES

- ❌ 6th/7th Gen. i3/i5/i7 cpu support
- Max. 32GB RAM
- 4x RS232/422/485
- 6x USB 3.0
- 2x USB2.0
- 2x 2.5" SATA HDD (RAID0/1 support)
- 9-36VDC



SPECIFICATIONS

CPU	:	LGA1151 socket 7th/6th gen Intel® Core™ i7/i5/i3 & Celeron® processor (CPU TDP max. up to 35 W)
Andet	:	4 x SMA type connector opening for antenna 1 x 9~36VDC power input connector 1 x ATX power switch 1 x Remote power switch 1 x AT/ATX quick switch 1 x Reset button
Chok/Vibration	:	3 Grms with CFast™ (5 - 500 Hz, X, Y, Z directions)
Digital I/O	:	32-channel programmable DI/DO
Dimensioner	:	280 x 190 x 70 mm (11.02" x 7.48" x 2.75")
Driftstemperatur	:	-40°C ~ +60°C (-40°F ~ +140°F) (with W.T. SSD, CPU TDP 35W)
Ethernet	:	4 x 10/100/1000 Mbps (Intel® i210IT, i219LM)
Forsyning	:	9~36VDC
Hukommelse	:	2 x 260-pin SO-DIMM DDR4-2133, up to 32 GB
IP-Tæthed	:	IP40
Lyd	:	Mic-in/Line-out
Materiale	:	Aluminum extrusion and heavy-duty steel

SPECIFICATIONS

OS SUPPORT	:	WE8S, WES7, Win10 IoT, Linux
Porte	:	4 x RS-232/422/485
Storage	:	2 x 2.5" SATA HDD with RAID 0&1 1 x CFast™ 1 x mSATA
Udgange	:	2 x HDMI (1 x HDMI 2.0 & 1 x HDMI 1.4b) 1 x DisplayPort
Udvidelser	:	2 x Full-size PCI Express Mini Card (USB + PCI Express signal) 1 x SIM slot
USB	:	6 x USB 3.0 2 x USB 2.0
Vægt	:	3.8 kg (8.37 lb)/ 4.6 kg (10.14 lb)
Watchdog	:	255 levels, 1 ~255 sec.