

19" LCD monitor med 300-nits, støv og spuletæt
IP54, dual AC/DC inputs,

FEATURES

19" LCD metal monitor, IP54 foran,
1280 x 1024
300 nits eller 1000 nits, 2000:1, 5:4
LED backlight
Responstid: 20ms
visnings vinkel: 178°/178°
1 x RS-232 (DB9 male)
1 x DVI-D (29-Pin DVI-D female)
1 x VGA (15-Pin D-sub female)
1 x RS232/422/485 (software selectable terminal
block)
Forsyning: 100 to 240 VAC, 24 VDC (18 to 30 V)
-15 to 55°C (5 to 131°F)
429 x 387 x 75 mm
Vægt: 7,800 g
RoHS, CRoHS, WEEE
Optional: RS-232: TxD, RxD, RTS, CTS, DTR, DSR,
DCD, GND
Optional: RS-422: Tx+, Tx-, Rx+, Rx-, GND
Optional: RS-485-2w: Data+, Data-, GND
Optional: RS-485-4w: Tx+, Tx-, Rx+, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Certifications	:	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V
Dimensioner	:	429 x 387 x 75 mm
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	1 x DVI-D, 1 x VGA
IP-Tæthed	:	IP54 (IP66 optional)
Kontrast	:	2000:1, 300 cd/m2, 5:4
Porte	:	1 x RS-232, RS-232/422/485 ports x 1, software-selectable (terminal block)
Vægt	:	7,800 g

