

Embedded fanless system med Celeron® CPU  
N3160 (1.6 Ghz/4core), op til 8GB, mSATA & SATA  
SSD el.HDD

## FEATURES

Omkostningseffektiv med blæserløs og kabelløs design  
Intel® Celeron® processor N3160 (1.6 GHz/4-core)  
2 x RS-232/422/485 porte  
4 x USB porte  
2 x isolated 10/100/1000 Mbps Ethernet porte  
1 x PoE PD kompatibel med IEEE 802.3at standard  
LAN 1  
1 x DIO port  
2 x PCI Express Mini Card slots (3G/GPRS & Wi-Fi)  
1 x mSATA & SATA SSD (or HDD)  
12 to 24 VDC  
Vægt: 1.50 KG  
Dimensioner: 48 x 110 x 155 mm  
DIN skinne og væg montering  
OS support: Windows® 7 Embedded, Windows® 8  
Embedded, Windows® 8, Windows® 10, Linux  
support package



**SPECIFICATIONS**

CPU	:	intel® Celeron® processor N3160 (1.6 GHz/4-core)
Farve	:	Sølv
BIOS	:	AMI UEFI BIOS
Beskyttelse	:	DC version OVP, reverse protection
Certifications	:	CE, FCC
Chok/Vibration	:	2 Gms (5 to 500Hz, amplitude 0.35 mm; operation/storage/transport)
Dimensioner	:	48 x 110 x 155 mm
Driftstemperatur	:	-20°C to +60°C
Harddisk	:	1 x mSATA 1 x SATA SSD (or HDD)
Hukommelse	:	1 x DDR3L-1600 SO-DIMM, op til 8GB
Luftfugtighed	:	10% to 95%
Montering	:	Din skinne og væg montering

## SPECIFICATIONS

OS SUPPORT	:	Windows® 7 Embedded Windows® 8 Embedded Windows® 8, Windows® 10 Linux support package
Porte	:	2 x RS-232/422/485 (COM 1/2) with DB9, 2 x USB 3.0, 2 x USB 2.0, 2 x 10/100/1000 Mbps Ethernet, DC terminal block: 12 to 24V DC-In, VGA (DB15 connector),
Software	:	AXView 2.0 Intelligent Remote Management Solution for IoT
Strømforsyning	:	DC terminal block: 12 to 24V DC-In PoE: IEEE 802.3at
Trådløs	:	1 x Full-size PCI Express Mini Card slot 1 x Full-size PCI Express Mini Card slot with mSATA 1 x SIM card socket 3 x Antenna
USB	:	2 x USB 3.0 2 x USB 2.0
Vægt	:	1.50 KG