

M485-CNV232-I

Optoisolated RS232 to RS422 / RS485 converter.
SELF-TUNING BAUD RATE ADJUSTING. RS232 is
isolated from PSU

FEATURES

- Optoisolated RS232 for RS422 / 485 Converter
3000vdc isolation
Up to 1.2 km on the RS422 / RS485
1.2kbit/s to 115.2 kbit/s, automatic baud rate
DB9 female connector for RS232 Signal
Screw terminals for RS422 / 485 signals
Supply 10 to 30 VDC



DANBIT A/S - Dansk Binær Teknik
Værkstedvej 39 Køge, 4600 Danmark

+45 56 66 20
20

salg@danbit.dk

M485-CNV232-I

SPECIFICATIONS

Afstand	:	Op til 1,2 km på RS422/485-siden
Data	:	1,2 til 115,2 kbit/s
Dimensioner	:	(W x H x D) 72 mm x 118 mm x 35 mm
Driftstemperatur	:	-25 °C ~ +75 °C
Forsyning	:	10 - 30 VDC 1,2 W
Features	:	Automatisk styring af TX Understøtter både halv og fuld duplex
Isolation	:	3000 VDC
Stik	:	RS232 DB9 hun og RS422/485 samt forsyning skrueterminaler