

## REP-SDI

SDI booster - DS1 video repeater over coax cable  
up to 200m

## FEATURES

- Overfør SDI-signalen op til 200 meter og op til 1200 meter med 5 i serie



## REP-SDI



## SPECIFICATIONS

Afstand	: SD-SDI (270/540Mbps) op til 400M (1000 meter v/ 5 REP-SDI) HD-SDI (1,45Gbps) op til 200M (1000 meter v/ 5 REP-SDI) Dual HD-SDI (2,97Gbps) op til 100M (500 meter v/ 5 REP-SDI)
Dimensioner	: 27 x 67 x 91 mm
Driftstemperatur	: 0° - 55° C, luftfugtighed 0 ~ 95 %
Indgang	: 1 x 75Ω BNC stik, RS485 Tx+, Tx- (skrueterminal)
Indikatorer og kontakter	: 1 x Power LED (grøn)
Opløsning	: HDTV input fra 480i til 1080p v/ 60Hz
Standarder	: SD-SDI (SMPTE 259M/344M), HD-SDI (SMPTE 292M), dual link HD-SDI (SMPTE 372M), og dual speed HD-SDI(SMPTE 424M)
Strømforsyning	: 230VAC til 12VDC 1,5 A strømforsyning medfølger
Udgange	: 1 x 75Ω BNC stik, RS485 Tx+, Tx- (skrueterminal)

