

24 "LCD monitor with 300-nits, capacitive touch, dust and leakproof IP54, IP20 rear, dual AC / DC inputs,

FEATURES

24 "LCD metal monitor, IP66 front, IP20 rear
1920 x 1080
300 nits, 5000: 1, 16: 9
LED backlight
Response time: 25ms
viewing angle: 178 ° / 178 °
Capacitive touch, 4 points
1 x RS-232 (DB9 male)
1 x DVI-D (29-pin DVI-D female)
1 x VGA (15 -Pin D-sub femlae)
1 x RS232 / 422/485 (software selectable terminal block)
Supply: 100 to 240 VAC, 24 VDC (18 to 30 V)
-15 to 55 ° C (5 to 131 ° F)
595 x 393 x 75 mm & nbsp;
Weight: 9.570 g
Desktop, Panel mounting, VESA mounting
Optional: RS-232: TxD, RxD, RTS, CTS , DTR, DSR, DCD, GND
Optional: RS-422: Tx +, Tx-, Rx +, Rx-, GND
Optional: RS-485-2w: Data +, Data, GND
Optional: RS-485-4w: Tx +, Tx-, Rx +, Rx-, GND



SPECIFICATIONS

Antal farver	:	16.7M (8-bit/color)
Certifications	:	IEC 61000-4-2 ESD: Contact: 4 kV; Air: 8 kV IEC 61000-4-3 RS: 80 MHz to 1 GHz: 3 V/m IEC 61000-4-4 EFT: Power: 1 kV; Signal: 0.5 kV IEC 61000-4-5 Surge: Power: 2 kV; Signal: 1 kV IEC 61000-4-6 CS: 1k V
Driftstemperatur	:	-15 to 55°C
Forsyning	:	100 to 240 VAC, 24 VDC (18 to 30 V)
I/O	:	1 x DVI-D, 1 x VGA
Kontrast	:	5000:1, 300 cd/m2, 16:9
Porte	:	1 x RS-232, RS-232/422/485 ports x 1, software-selectable (terminal block)
Touch	:	Capacitive touch, 4 points
Weight	:	9,570 g